

ZEETEX OUTBOARD MOTOR OIL

PERFORMANCE LEVEL:
it meets and exceeds the requirement of NMMA TC-W3

- ZEETEX OUTBOARD MOTOR OIL is a premium performance two stroke, marine outboard engine oil. It is formulated with ashless additive package and high viscosity index base stock.
- ZEETEX OUTBOARD MOTOR OIL is recommended for all types of gasoline fuel two stroke marine outboard engines. It can also be mixed with fuel to oil ratio up to 50:1, or as recommended by the engine manufacturer. It is not recommended for use in any four stroke engine.
- ZEETEX OUTBOARD MOTOR OIL is a premium quality oil with enhanced ashless property to resist harmful deposits in the combustion chamber. It gives protection against pre-ignition and helps to avoid spark plug fouling, under all operating conditions, and also provides excellent protection in metal wear and ensures longer engine life. The ashless additive system provides superior piston cleanliness and protection against ring sticking by minimizing deposit formation, thus maintaining combustion efficiency and protection against power loss.

PHYSICAL CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
Specific Gravity @ 60/60 °F	ASTM D-4052	0.860
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	36
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	6.5
Viscosity Index	ASTM D-2270	130
Flash Point, COC, °C	ASTM D-92	96
Pour Point °C	ASTM D-97	-35
Sulphated Ash, %wt	ASTM D-874	<0.01