

ZEETEX EP GEAR OIL

SAE GRADE: 80W/90, 85W/140, 90, 140

PERFORMANCE LEVEL:

API classification: GL-4

U.S. Military specification: MIL-L-2105

- ZEETEX EP GEAR OIL is an automotive gear lubricant and is recommended for manual transmission, drive axle, and final drive of automobile, heavy-duty earth moving agricultural and construction equipment. It is formulated for use in bevel, spiral bevel helical and hypoid enclosed gear boxes operating under mild load and normal operating conditions.
- ZEETEX EP GEAR OIL is formulated with solvent refined paraffinic base stock and Sulphur Phosphorous based additive package. It has good resistance to oxidation, rust and corrosion, and contains highly effective defoamant.
- ZEETEX EP GEAR OIL maintains fluid film on moving parts which provides excellent protection against metal wear.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE			
		80W/90	85W/140	90	140
Specific Gravity @ 60/60 °F	ASTM D-4052	0.885	0.90	0.888	0.906
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	152	410	170	425
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	15	28	16	29
Viscosity Index	ASTM D-2270	98	99	97	97
Flash Point, COC, °C	ASTM D-92	220	240	230	250
Pour Point °C	ASTM D-97	-27	-24	-9	-9
Foam Sequence I (ml)	ASTM D-892	5/0	10/0	0/0	0/0
Foam Sequence II (ml)	ASTM D-892	10/0	10/0	10/0	10/0
Foam Sequence III (ml)	ASTM D-892	5/0	10/0	0/0	0/0